

0 601 063 N80 – GLL 5-50 X

Material number	0 601 063 N80
EAN	6938032700039
1 x shoulder strap 2 608 000 706	✓
4 x 1.5 V LR6 battery (AA)	✓
Carrying bag	✓



Technical data

Technical data

Laser diode	630 – 650 nm, < 1mW
Operating temperature	-10 – 45 °C
Storage temperature	-20 – 70 °C
Laser class	2
Working range, value	15 m
Working range	15 m
Working range with receiver, value	50 m
Working range with receiver	50 m
Accuracy	Horizontal laser line: ± 0.2 mm/m* ; Vertical laser lines: ± 0.3 mm/m* (*plus use-dependent deviation)
Working range of laser points, max.	5 m (bottom)
Self-levelling range	$\pm 3^\circ$
Levelling time	4 s
Power supply	4 x 1.5 V LR6 (AA)
Operating time (max.)	24 h
Tripod thread	5/8"
Weight, approx.	0.5 kg
Colour of laser line	red
Color of plumb points	red
Plumb point accuracy	± 0.7 mm/m* (*plus use-dependent deviation)

Sales information

Positioning

- Better line visibility for increased work efficiency in everyday interior levelling jobs

User benefit

- Greater Visibility - On front cross for better working performance
- Compact - Light and easy-to-carry
- Robust - Thanks to the highly sophisticated Bosch pendulum precision system (PPS) which further enhances tool protection and levelling accuracy