

0 601 217 1F3 – GSB 13 RE

Material number	0 601 217 1F3
EAN	3165140548106
Auxiliary handle 1 602 025 024	✓
Depth stop 210 mm 1 613 001 010	✓
Keyed chuck 13 mm 2 608 571 079	✓



Technical data

Technical data

Rated input power	600 W
No-load speed, 1st gear	0 – 2,800 rpm
Power output	301 W
Weight	1.8 kg
Rated torque	1.8 Nm
Drill spindle connecting thread	1/2"-20 UNF
Chuck capacity, min./max.	1.5 – 13 mm
Tool dimensions (length)	266 mm
Tool dimensions (height)	180 mm
Impact rate at no-load speed	0 – 44,800 bpm



Drilling range

Drilling diameter in wood	25 mm
Drilling diameter in steel	10 mm
Drilling diameter in masonry	15 mm

Noise/vibration information

Sound pressure level	97 dB(A)
Sound power level	108 dB(A)
Uncertainty K	5 dB
Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level dB(A); Sound power level dB (A). Uncertainty K= dB.

Sales information

Positioning

- Compact power – The most compact and powerful impact drill in its class

User benefit

- Robust and powerful 600 W motor
- Extremely handy: No bigger than a glove and 1.7 kg light
- Soft in line grip for a secure hold