

# 0 601 217 1F8 – GSB 600 RE

Material number	0 601 217 1F8
EAN	3165140596138
Tool box 2 609 160 136	✓



## Technical data

### Technical data

Rated input power	600 W
No-load speed, 1st gear	0 – 2,800 rpm
Power output	301 W
Weight	1.8 kg
Rated torque	1.8 Nm
Drill spindle connecting thread	1/2"-20 UNF
Chuck capacity, min./max.	1.5 – 13 mm
Tool dimensions (length)	266 mm
Tool dimensions (height)	180 mm
Impact rate at no-load speed	0 – 44,800 bpm

### Drilling range

Drilling diameter in wood	25 mm
Drilling diameter in steel	10 mm
Drilling diameter in masonry	15 mm

### Noise/vibration information

Sound pressure level	97 dB(A)
Sound power level	108 dB(A)
Uncertainty K	5 dB
Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level dB(A); Sound power level dB (A). Uncertainty K= dB.



## Sales information

---

### Positioning

- Compact power – The most compact and powerful impact drill in its class

### User benefit

- Robust and powerful 600 W motor
- Extremely handy: No bigger than a glove and 1.7 kg light
- Soft in line grip for a secure hold