

0 601 9F8 3F0 – GSB 180-LI

Material number	0 601 9F8 3F0
EAN	4059952576213
2 x battery GBA 18V 2.0Ah 1 600 A00 1CG	✓
Carrying case	✓
Quick charger GAL 18V-40 Professional 1 600 A01 9RM	✓



Technical data

Technical data

Torque (soft/hard/max.)	21/54/- Nm
No-load speed (1st gear / 2nd gear)	0 – 500 / 0 – 1,900 rpm
Battery type	Lithium-ion
Max. impact rate	27.000 bpm
Chuck capacity, min./max.	1.5 / 13 mm
Battery voltage	18.0 V
Torque settings	20+2
Tool dimensions (width)	62 mm
Tool dimensions (length)	210 mm
Tool dimensions (height)	224 mm
Product category subdivision	Cordless Combi

Drilling diameter

Max. drilling diameter in wood	35 mm
Max. drilling diameter in steel	10 mm
Max. drilling diameter in masonry	10 mm

Screw diameter

Max. screw diameter	10 mm
---------------------	-------

Noise/vibration information

Sound pressure level	88 dB(A)
Sound power level	99 dB(A)
Uncertainty K	5 dB
Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level 88 dB(A); Sound power level 99 dB(A). Uncertainty K= 5 dB.



Sales information

Positioning

- More power. More Robust.

