

0 601 9G8 1F2 – GSB 120-LI

Material number	0 601 9G8 1F2
EAN	4053423226119
2 x battery GBA 12V 2.0Ah 1 600 A00 1BT	✓
23-piece drilling and screwdriving bit set with holder	✓
Carrying case	✓
Charger GAL 12V-20 Professional	✓



Technical data

Technical data

Torque (soft/hard/max.)	14/30/- Nm
No-load speed (1st gear / 2nd gear)	0 – 400 / 0 – 1,500 rpm
Battery type	Lithium-ion
Max. impact rate	22.500 bpm
Chuck capacity, min./max.	0.8 / 10 mm
Weight excl. battery	0.9 kg
Torque settings	20+2
Tool dimensions (width)	53 mm
Tool dimensions (length)	170 mm
Tool dimensions (height)	188 mm
Product category subdivision	Cordless Combi



Drilling diameter

Max. drilling diameter in wood	20 mm
Max. drilling diameter in steel	10 mm
Max. drilling diameter in masonry	8 mm

Screw diameter

Max. screw diameter	8 mm
---------------------	------

Noise/vibration information

Sound pressure level	82.5 dB(A)
Sound power level	93.5 dB(A)
Uncertainty K	3 dB
Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level 82.5 dB(A); Sound power level 93.5 dB(A). Uncertainty K= 3 dB.



Sales information

Positioning

- Highly flexible, highly economical

User benefit

- Power and flexibility within reach for screwdriving and drilling
- 2-speed gearbox enables high productivity and excellent torque
- Electronic Cell Protection for longer battery life and more durability