0 611 338 7F0 - GSH 500

| Material number | 0 611 338 7F0 |
|--|---------------|
| EAN | 4059952513775 |
| 1 x pointed chisel, SDS max, 280 mm 1 618 600 023 | √ |
| Auxiliary handle 1 619 P14 935 | ✓ |
| Carrying case | ✓ |



Technical data

Technical data

| Rated input power | 1.100 W |
|---|--------------------------------|
| Impact energy (according to EPTA 05/2016) | 7.8 J |
| Impact rate at rated speed | 2,900 bpm |
| Weight | 5,7 kg |
| Tool dimensions (width) | 103 mm |
| Tool dimensions (length) | 460 mm |
| Tool dimensions (height) | 235 mm |
| Tool holder | SDS max |
| Product category subdivision | Demolition Hammer with SDS max |





Noise/vibration information

| Noise level | The A-rated noise level of the power tool is typically as follows: Sound pressure level dB(A); Sound power level dB |
|-------------|---|
| | (A). Uncertainty K= dB. |

Sales information

Positioning

■ Fast & Reliable - The NEW Chipping Specialist!

User benefit

- Great efficiency: High impact energy coupled with superior impact rate resulting in high chipping output
- Extended durability: Grease sealing ring to prevent leakage coupled with dust cap solution for better dust proof resulting long life time
- Ergonomic design: One hand Vario Lock design for 12 position chisel bit change, lock-on button for daily continuous work

