

SMART DIGITAL METER
11S



AC / DC Voltage

NCV

Back light

Frequency

Torch

Resistance

Smart DM

Continuity

Low Battery Indication

Over Range Display

CAT III
600V

- FEATURES :
- ✓ 3½ DIGITS
 - ✓ 3,999 COUNTS
 - ✓ TRUE RMS
 - ✓ NCV
 - ✓ LIVE WIRE DETECTION
 - ✓ AUTO POWER OFF (APO)
 - ✓ SMART DIGITAL METER (AUTO MODE)

DC VOLTAGE

RANGE	RESOLUTION	ACCURACY
4V	0.001 V	±(0.5% +3) Impedance Approx 10MΩ
40V	0.01 V	
400V	0.1 V	
600V	1 V	

AC VOLTAGE

RANGE	RESOLUTION	ACCURACY
4V	0.001 V	±(0.8%+3) Impedance Approx 10MΩ Frequency Response 40 Hz±1 KHz:TRMS
40V	0.01 V	
400V	0.1 V	
600V	1 V	

FREQUENCY

RANGE	RESOLUTION	ACCURACY
4 Hz	0.001 Hz	±(1.0 + 3)
40 Hz	0.01 Hz	
400 Hz	0.1 Hz	
4 KHz	0.001 KHz	
40 KHz	0.01 KHz	
200 KHz	0.1 KHz	

CONTINUITY

	<Approx 50Ω Buzzer will sound and indicator light will be on
--	--

RESISTANCE

RANGE	RESOLUTION	ACCURACY
400Ω	0.1Ω	±(1.0 + 5)
4KΩ	0.001KΩ	
40KΩ	0.01KΩ	
400KΩ	0.1KΩ	
4MΩ	0.001MΩ	
40MΩ	0.01MΩ	

POWER : AAA 1.5V x 2

Dimension	: H127 x W66 x D19 mm
Weight	: Approx 107g.
Accessories	: Test leads, User Manual & Battery
Qty	: 50 Pcs. in a Box