



126B+TRMS



135B+TRMS



Pocket Size

**TRMS, Auto / Manual, 4 Digits 9999 Counts LCD with Backlight, APO, Capacitance, Resistance, Frequency, Duty Cycle & Square Wave Output**

**Ranges**

**DC Voltage** 9.999 / 99.99 / 999.9mV /

9.999 / 99.99 / 999.9V

Accuracy ± [0.5% rdg + 3 dgt]

**AC Voltage** <sup>TRMS</sup> 9.999 / 99.99 / 999.9mV /  
9.999 / 99.99 / 750.0V

Accuracy ± [1.0% rdg + 3 dgt]

AC Response 40Hz ~ 1KHz

**DC Current** 99.99 / 999.9µA

999.9mA / 9.999A

Accuracy ± [0.8% rdg + 3 dgt]

on 99.99 / 999.9µA

± [1.0% rdg + 3 dgt]

on 999.9mA / 9.999A

**AC Current** <sup>TRMS</sup> 99.99 / 999.9µA

999.9mA / 9.999A

Accuracy ± [1.0% rdg + 3 dgt]

on 99.99 / 999.9µA

± [1.2% rdg + 3 dgt]

on 999.9mA / 9.999A

AC Response 40Hz ~ 1KHz

**Resistance** 99.99 / 999.9Ω / 9.999 /

99.99 / 999.9KΩ / 9.999MΩ

Accuracy ± [1.0% rdg + 3 dgt]

on 99.99Ω

± [0.5% rdg + 3 dgt]

on 999.9Ω / 9.999 /

99.99 / 999.9KΩ

± [1.5% rdg + 3 dgt]

on 9.999MΩ

**Capacitance** 9.999 / 99.99 / 999.9nF /

9.999 / 99.99 / 999.9µF /

9.999mF

Accuracy ± [5.0% rdg + 20 dgt]

on 9.999nF

± [2.0% rdg + 5 dgt]

on 99.99 / 999.9nF /

9.999 / 99.99 / 999.9µF

± [5.0% rdg + 5 dgt]

on 9.999mF

**Frequency** 99.99Hz ~ 9.999MHz

**TRMS, Auto / Manual, 4 Digits 9999 Counts LCD with Backlight, APO, Capacitance, Resistance, NCV, Frequency, Duty Cycle & Temperature**

**Ranges**

**DC Voltage** 9.999 / 99.99 / 999.9mV /

9.999 / 99.99 / 999.9V

Accuracy ± [0.5% rdg + 3 dgt]

**AC Voltage** <sup>TRMS</sup> 9.999 / 99.99 / 999.9mV /  
9.999 / 99.99 / 750.0V

Accuracy ± [1.0% rdg + 3 dgt]

AC Response 40Hz ~ 1KHz

**DC Current** 99.99 / 999.9µA

999.9mA / 9.999A

Accuracy ± [0.8% rdg + 3 dgt]

on 99.99 / 999.9µA

± [1.0% rdg + 3 dgt]

on 999.9mA / 9.999A

**AC Current** <sup>TRMS</sup> 99.99 / 999.9µA

999.9mA / 9.999A

Accuracy ± [1.0% rdg + 3 dgt]

on 99.99 / 999.9µA

Accuracy ± [0.1% rdg + 2 dgt]

**Duty Cycle** 1% ~ 99%

Accuracy ± [0.1% rdg + 2 dgt]

**Square Wave** 50Hz / 100Hz / 200Hz /

300Hz / 400Hz / 500Hz /

600Hz / 700Hz / 800Hz /

900Hz / 1000Hz / 2000Hz /

3000Hz / 4000Hz / 5000Hz

CAT II 1000V, CAT III 600V

**Measuring**

**Category**

**SP Function** Diode Test, Audible

Continuity, Data Hold

**Power** Two 1.5V 'AAA' Battery

**Low Battery** 'L' is indicated

**Battery Life** 200 hours typical

**Dimensions** 130 x 65 x 32mm (approx.)

**Weight** 130gms Including Battery

(approx.)

**Accessories** One Pair of Test Leads,

Drawstring Pouch,

Battery (installed),

Instruction Manual

**AC Response** ± [1.2% rdg + 3 dgt]  
on 999.9mA / 9.999A  
40Hz ~ 1KHz

**Resistance** 99.99 / 999.9Ω / 9.999 /  
99.99 / 999.9KΩ / 9.999 /  
99.99MΩ

Accuracy ± [1.0% rdg + 3 dgt]

on 99.99Ω

± [0.5% rdg + 3 dgt]

on 999.9Ω / 9.999 /

99.99 / 999.9KΩ

± [1.5% rdg + 3 dgt]

on 9.999 / 99.99MΩ

**Capacitance** 9.999 / 99.99 / 999.9nF /

9.999 / 99.99 / 999.9µF /

9.999mF

Accuracy ± [5.0% rdg + 20 dgt]

on 9.999nF

± [2.0% rdg + 5 dgt]

on 99.99 / 999.9nF /

9.999 / 99.99 / 999.9µF

± [5.0% rdg + 5 dgt]

on 9.999mF

**Frequency** 99.99Hz ~ 9.999MHz

Accuracy ± [0.1% rdg + 2 dgt]

**Duty Cycle** 1% ~ 99%

Accuracy ± [0.1% rdg + 2 dgt]

**Temperature** -20°C ~ 1000°C /

-4°F ~ 1832°F

Accuracy ± [2.5% rdg + 5 dgt]

**Measuring** CAT II 1000V, CAT III 600V

**Category**

**SP Function**

**Power**

**Low Battery**

**Battery Life**

**Dimensions**

**Weight**

**Accessories**

Diode Test, Audible

Continuity, Data Hold

Two 1.5V 'AAA' Battery

'L' is indicated

200 hours typical

130 x 65 x 32mm (approx.)

130gms Including Battery

(approx.)

One Pair of Test Leads,

Drawstring Pouch,

Battery (installed),

Instruction Manual &

K Type Thermocouple

(upto 260°C)