

**UNI-T**<sup>®</sup>

Instruments.uni-trend.com



# Data Sheet

## UT3550 Serie Battery Tester



## Main Features

- High-accuracy: resistance 0.5%/ voltage 0.05%
- Resistance measurement range: 0.001m Ω ~ 30.00 Ω
- Voltage measurement range: 0.0001V ~ 100.000V
- Resolution: resistance: 0.001mΩ voltage: 0.1mV
- Comparison mode: SEQ, PER, ABS
- The new AC internal resistance test method can measure almost all types of batteries
- 3.5-inch LCD main display
- 0.96 inch auxiliary display screen
- UPS can be measured directly online
- USB data storage and screenshot saving function
- Lithium battery power supply (2000mAh)
- Provide type C interface to realize remote control
- Support SCPI protocol
- Protection grade IP65

# Battery Tester Panel



- ① 3.5 inch LCD
- ② Function keys
- ③ Power switch
- ④ Test terminals
- ⑤ Function shortcuts
- ⑥ Numeric keypad
- ⑦ Type-C interface
- ⑧ USB interface
- ⑨ Power Socket
- ⑩ 0.96 inch sub-display
- ⑪ Replaceable clip



# Product Introduction

UT3550 is a hand-held battery tester with automatic real-time detection. It has the portability of handheld instruments and the superior performance of Bench instruments. It is a measuring instrument with high accuracy and high resolution. Equipped with USB type C interface for remote control and data acquisition and analysis. Support SCPI protocol. It is mainly used in the quality inspection of various batteries. UPS can be directly measured online with high accuracy.

## Wide measuring range

UT3550 battery tester resistance measurement range: 0.001mΩ~30.00Ω。Voltage measurement range: 0.0001V ~ 100.00V。The measuring range is wider than that of the common handheld internal resistance meter. More kinds of battery products can be measured.



## Filtering function

UT3550 has three comparison methods: direct reading, percentage, and absolute value. It can be set according to the measurement object to help you screen out defective products. The filtering results shall be clearly and specifically marked.



## Dual screen display

This handheld internal resistance tester has two screen displays. 3.5inch main screen, displaying detailed information. The auxiliary screen is located at the top, which is convenient to carry and read

quickly during measurement. Save you valuable time.




## On-line measurement

UT3550 adopts AC method to measure internal resistance, which can measure a wide range of batteries. It can be measured during the working process of the battery without affecting the measurement accuracy and stability. It is also applicable to UPS measurement.



## Remote control

The UT3550 uses the type C interface to connect the upper computer, so as to realize remote control. With the host computer software, the data record and filtering can be displayed at the same time. Support SCPI protocol, which can be applied to automatic construction.



## Automatic recording

UT3550 can set the timer value to start the automatic recording process. Up to 500 test data can be recorded. You can export CSV files and do

data analysis on the computer.



## Technical Specification

Function	Range name	Range	Resolution	Accuracy	Measuring current	Description
Resistance Measurement	0			±0.5%rdg ±5dgt	150mA 15mA 1.5mA 150µA	Measuring current frequency: 1kHz±30Hz
	1	30mΩ	10µΩ			
	2	300mΩ	100µΩ			
	3	3Ω	1mΩ			
	4	30Ω	10mΩ			
Voltage Measurement	0	10V	100µV	±0.05%rdg ±5dgt	/	
	1	100V	1mV			
Display	3.5 inch LCD display +0.96 inch OLED on the top					
Range Mode	Auto and Manual (resistance and voltage)					
Calibration	Short circuit full range to zeroed					
Testing Speed	1/s (manual range)					
Filter function	It has three output situations: exceed resistance and voltage upper limit/ exceed resistance and voltage low limit and conform					
Beep	OFF, OK, NG					
Comparison Mode	Absolute deviation (ABS) , Relative deviation (PER)					
	Direct-reading (SEQ)					
Other Function	Lock keypad, U disk storage, keypad tone, Chines/English language, screenshot					
Test Terminal	Four-terminal test method					
Trigger	Internal, manual and remote trigger					
Storage	Internal 500 groups, exportable CSV files					
Interface	Type-c interface (communication)/USB DEVICE (storage) /charge interface					
Upper-computer Software	SCPI					
Charging Time	<5 hour					
Operating Time	About 5 hour (20% brightness display)					
Power	The maximum 5VA					
Power Supply	7.4V, 2000mAh rechargeable lithium battery or 9VDC 2A power adapter					
Preheating Time	At least 15 minute					
Temperature/Humidity Index	Temperature: 18C~28C, Humidity: <65%RH					
Operating Temperature/Humidity	Temperature: 0C~40C, Humidity: 10~80%RH					
Storage Temperature/Humidity	Temperature: -20C~60C, Humidity: 10~90%RH					
Temperature Index	Over 28 C, less 18 C, each degree plus 0.1* the specified precision					
Operating Altitude	≤2000m					



\*The UT3550 series have been certified by CE, cETLus.

## Standard accessories

Power adapter	1	9V 2000mA switching power adapter wire length 1200mm round pin (RoHS)
Soft carrying case	1	Black, with "UNI-T" logo/RoHS
Shoulder strap	1	Black
USB communication cable type-C	1	USB2.0, type C data wire
With magnetic hanging belt	1	Black, long about 40cm, width about 2.5cm/RoHS
UT3550 Kelvin test clip	1	Crocodile clip red and black test line (with sheath)(RoHS)

## Warranty

Three-years warranty, excluding probes and accessories.

Please visit [https://instruments.uni-trend.com/list\\_190/65.html](https://instruments.uni-trend.com/list_190/65.html) to learn more information.

To protect your investment, please purchase from UNI-T official authorized global distributors.

## Find a Distributor

Find an authorized distributor here: <https://instruments.uni-trend.com/Network>

## Contact UNI-T

E-mail: [info@uni-trend.com](mailto:info@uni-trend.com)

Test & Measurement Instruments Website: [instruments.uni-trend.com](https://instruments.uni-trend.com)

UNI-T Corporate Website: [www.uni-trend.com](https://www.uni-trend.com)

UNI-T group maintains a wide products category includes Digital Test & Measurement instruments, Field Testing Meter, Infrared thermal imaging products. As early as 2008, we continue to introduce self-developed Digital Test and Measurement instruments to the market and have made remarkable achievements. At present, we have formed a variety of product lines of Oscilloscope, AWG, Spectrum Analyzer, Bench Multi-meter, Power Supply, DC Load, Power Meter, LCR Meter, Micro Ohm Meter and Data logger. We have separated instruments sub-sites, [instruments.uni-trend.com](http://instruments.uni-trend.com), on the basis of the original website [www.uni-trend.com](http://www.uni-trend.com), in order to be more targeted to provide customers with better service and value.

UNIT/MKT-TMI-SC/AL-2205-028

[Instrument.uni-trend.com](http://Instrument.uni-trend.com)

**UNI-T**<sup>®</sup>