

CM-2000

Features:

- 3½ Digit
- 2000 Count
- Non Contact Voltage (NCV)
- Clamp Torch
- Jaw Open: 28mm
- Auto Power Off (APO)
- True RMS



DC VOLTAGE

Range	Resolution	Accuracy
200mV	0.1mV	±0.5% of rdg + 5 digits
2V	1mV	
20V	10mV	
200V	100mV	
600V	1V	±1.0% of rdg + 5 digits

AC VOLTAGE

Range	Resolution	Accuracy
200mV	0.1mV	± 1.5% of rdg + 10 digits
2V	1mV	± 1.0% of rdg + 5 digits
20V	10mV	
200V	100mV	
600V	1V	± 1.2% of rdg + 5 digits

AC CURRENT

Range	Resolution	Accuracy
2A	1mA	±3.0% of rdg + 5 digits
20A	10mA	±2% of rdg + 5 digits
200A	100mA	
600A	1A	

RESISTANCE

Range	Resolution	Accuracy
200Ω	0.1Ω	±0.8% of rdg + 5 digits
2kΩ	1Ω	±0.8% of rdg + 1 digits
20kΩ	10Ω	
200kΩ	100Ω	
2MΩ	1KΩ	
20MΩ	10KΩ	±1.2% of rdg + 5 digits

TEMPERATURE

Range	Resolution	Accuracy
(-40~750)°C	1°C	<400°C ±1.0% of rdg + 5 digits
		≥400°C ±1.5% of rdg + 15 digits

POWER

AAA1.5V X 2

- Standard Accessories : Test Lead, Manual, Soft Carrying Case
- Dimension : 230(H) x 80(W) x 37(D)mm