

**Features:**

- 3½ Digit Clamp Meter with Backlight Manual Range
- 1999 Count
- Fully Protected in all RANGE
- Jaw Open: 52mm

- Clamp Torch
- True RMS
- NCV

**AC VOLTAGE**

Range	Resolution	Accuracy
20V	10mV	±1.0% of rdg + 5 digits
750V	1V	±1.2% of rdg + 5 digits

**DC VOLTAGE**

Range	Resolution	Accuracy
200mV	0.1mV	±0.5% of rdg + 5 digits
20V	10mV	
1000V	1V	±1.0% of rdg + 5 digits

**TEMPERATURE**

Range	Resolution	Accuracy
(-40-1000)°C	1°C	±1.0% of rdg + 5 digits

**AC CURRENT**

Range	Resolution	Accuracy
200A	0.1A	±2.0% of rdg + 5 digits
1000A	1A	

**RESISTANCE**

Range	Resolution	Accuracy
200Ω	0.1Ω	±0.8% of rdg + 5 digits
2kΩ	1Ω	
20kΩ	10Ω	
200kΩ	100Ω	±0.8% of rdg + 1 digit
2mΩ	1kΩ	
20mΩ	10kΩ	±1.2% of rdg + 5 digits
200mΩ	100Ω	

**POWER**

AAA1.5 x 2

**Special Function**

Diode Test	✓
Continuity Test	✓
Function Protection	✓
Sampling Rate	2 or 3 times/sec
Input Impedance	10MΩ

- Standard Accessories :  
Soft Carrying Case, Manual, Test Lead
- Dimension :  
123(H) x 270(W) x 35(D)mm

