

# CM-2070FT

## Features:

- 3¾ Digit Clamp Meter with Backlight
- 4000 Count
- Full Function Protection, Strong anti-interferential Performance
- Temperature & Non Contact Voltage (NCV) • Frequency Test
- Clamp Torch • Jaw Open : 52mm

### DC VOLTAGE

Range	Resolution	Accuracy
400mV	0.1mV	±1.0% of rdg + 5 digits
4V	1mV	
40V	10mV	±0.5% of rdg + 5 digits
400V	100mV	
1000V	1V	±1.0% of rdg + 5 digits

### CAPACITANCE

Range	Resolution	Accuracy
4nF	1pF	±5.0% of rdg - 20 digits
40nF	10pF	
400nF	100pF	±3.5% of rdg + 10 digits
4µF	1nF	
40µF	10nF	
200µF	100nF	±5.0% of rdg + 10 digits

### RESISTANCE

Range	Resolution	Accuracy
400Ω	0.1Ω	±0.8% of rdg + 5 digits
4kΩ	1Ω	
40kΩ	10Ω	
400kΩ	100Ω	±0.8% of rdg + 3 digits
4MΩ	1KΩ	
40MΩ	10KΩ	±1.2% of rdg + 5 digits

### AC VOLTAGE

Range	Resolution	Accuracy
400mV	0.1mV	±1.5% of rdg + 5 digits
4V	1mV	
40V	10mV	±1.0% of rdg + 5 digits
400V	100mV	
750V	1V	±1.5% of rdg + 5 digits

### FREQUENCY

Range	Resolution	Accuracy
100Hz	0.01Hz	
1kHz	0.1Hz	
10kHz	1Hz	±0.5% of rdg + 5 digits
100kHz	10Hz	
1MHz	100Hz	
10MHz	1kHz	

### TEMPERATURE

Range	Resolution	Accuracy
(-40-1000)°C	1°C	+400°C ±1.2% of rdg + 3 digits +60°C ±1.3% of rdg + 15 digits

- Standard Accessories :  
Test lead, Manual, Soft Carrying Case  
TP04 Temperature probe
- Dimension :  
123(H) x 270(W) x 35(D)mm

### AC CURRENT

Range	Resolution	Accuracy
400A	100mA	
1000A	1A	±2.0% of rdg + 5 digits

POWER 9V (6F22) X 1

