

Manufacturer	Hioki
Model No	CM4373-50
Measuring Parameters	DC Current, AC Current, Crest Factor, DC Voltage, AC Voltage, Resistance, Capacitance, Frequency, and Temperature
DC Current	600.0 A/2000 A
Accuracy	±1.3%
AC Current	600.0 A/2000 A (10 Hz to 1 kHz, True RMS)
Accuracy	45 - 66 Hz
Crest factor	600.0 A range: 3 or less 2000 A range: 2.84 or less
DC+AC Current range	600.0 A/2000 A (10 Hz to 1 kHz, True RMS)
Accuracy	45-66 Hz
DC Voltage	600.0 mV to 1000 V (When using P2000: 600.0 V to 2000 V)
AC Voltage	6.000 V to 1000 V, 4 ranges (15 Hz to 1 kHz, True RMS)
Accuracy	45 - 66 Hz
DC+AC Voltage	6.000 V to 1000 V, 4 ranges
Resistance	600.0 Ω to 6.000 MΩ, 5 ranges
Accuracy	±0.7%
Capacitance	1.000 μF to 1000 μF, 4 ranges
Accuracy	±1.9%
Frequency	9.999 Hz to 999.9 Hz, 3 ranges
Accuracy	±0.1%
Temperature	-40.0 to 400.0 °C
Voltage detection	Hi: 40 V to 600 V AC, Lo: 80 V to 600 V AC, 50/60 Hz
Enclosure	IP54
Supply Scope	Test Lead L9300, Carrying Case C0203, LR03 Alkaline battery ×2, Instruction Manual×2, Operating Precautions ×1
Dimensions	65 mm × 250 mm × 35 mm
Weight	530 g