

Features:

- 3½ Digit Manual Multimeter
- Live Wire Recognition
- Live Remote Control Testing
- Full Overload Protection
- 1,999 Count
- True RMS

DC VOLTAGE

Range	Resolution	Accuracy
200mV	0.1mV	±1.2% of rdg 5 digits
2V	1mV	
20V	10mV	
200V	100mV	
1000V	1V	±1.5% of rdg 5 digits

DC CURRENT

Range	Resolution	Accuracy
20mA	10µA	±1.5% of rdg 5 digits
200mA	100µA	±2% of rdg 5 digits
10A	10mA	±3% of rdg 5 digits

AC VOLTAGE

Range	Resolution	Accuracy
20V	10mV	±1.5% of rdg 5 digits
200V	100mV	
750V	1V	±2% of rdg 7 digits

AC CURRENT

Range	Resolution	Accuracy
20mA	10µA	±2.5% of rdg 5 digits
200mA	100µA	
10A	10mA	±3% of rdg 7 digits

TRANSISTOR hFE TEST (0-1000)

Range	Description Display:	Measuring Condition	
hFE	0~1000β	I _{bo} ≈10µA	V _{ce} ≈2.8V

RESISTANCE

Range	Resolution	Accuracy
200Ω	0.1Ω	±1.5% of rdg 5 digits
2KΩ	1Ω	
20KΩ	10Ω	
200KΩ	100Ω	
2MΩ	1KΩ	
20MΩ	10KΩ	±2% of rdg 5 digits
200MΩ	100KΩ	±5% of rdg 10 digits

CAPACITANCE

Range	Resolution	Accuracy
20nF	10p	±4% of rdg 25 digits
200nF	100pF	±4% of rdg 15 digits
2µF	1nF	
200µF	10nF	

FREQUENCY

Range	Resolution	Accuracy
2kHz	0.001kHz	±1.5% of rdg 10 digits
200kHz	0.1kHz	

Special Function

Diode Test	✓	Continuity Buzzer	Approx. < 50Ω
Transistor Testing	✓	Auto Power OFF	Approx. 15min.

Power AA1.5V x 2

- Standard Accessories: Test Lead, Manual
- Dimension : 175(H) x 83(W) x 31(D)mm

DM-81

