

# DM - 830L



## Features:

- 3 ½ Digit Manual Multimeter with Backlight
- 1,999 Count
- Data Hold
- Transistor & Diode Test
- Overload Protection
- Low Battery Indication
- CAT II 600V

### DC VOLTAGE

Range	Resolution	Accuracy
200mV	100μV	±0.5% of rdg + 2 digits
2V	1mV	
20V	10mV	
200V	100mV	±0.8% of rdg + 2 digits
600V	1V	

### AC VOLTAGE

Range	Resolution	Accuracy
200V	100mV	±1.2% of rdg + 10 digits
600V	1V	

### RESISTANCE

Range	Resolution	Accuracy
200Ω	0.1Ω	±0.8% of rdg + 3 digits
2kΩ	1Ω	±0.8% of rdg + 2 digits
20kΩ	10Ω	
200kΩ	100Ω	±1.0% of rdg + 2 digits
2MΩ	1KΩ	

### DC CURRENT

Range	Resolution	Accuracy
200μA	0.1μA	±1% of rdg + 2 digits
2mA	1μA	
20mA	10μA	
200mA	100μA	±1.5% of rdg + 2 digits
10A	10mA	±3% of rdg + 2 digits

### POWER

9V (6F22) x 1

### TRANSISTOR hFE TEST (0-1000)

Range	Test Range	Test Current	Test Voltage
NPN & PNP	0-1000	1b=10μA	Vce=3V

- Standard Accessories : Manual, Test lead
- Dimension : 69(H) x 138(W) x 31(D)mm