



DT-1

- Measuring range : -50~330°C -58~662°F (DT-1)
50~300°C -58~626°F (DT-2)
- Accuracy : ±0.5% ± 1°C/1.8°F
- Resolution : 0.1°C/0.1°F
- Probe Length : 145MM
- °C and °F selection
- Auto Power Off (APO)
- Water - Resistant
- Water Proof Level IP-54 (Only for DT-1)
- Power : 3 V "CR 1225" Button Cell (DT-1)
- Power : 1.5 V "AG 13" (DT-2)



DT-2

DT-302-1/DT-302-2



Features:

- Large LCD display makes reading clear
- Data Hold Function
- High Resolution
0.1°C/°F (DT-302-1/2)
- High Stability, high accuracy
0.2% (DT-302-1)
0.5% (DT-302-2)

Technical Data :

Basic Functions	Range	Accuracy	
		DT-302-1	DT-302-2
Temperature Range	-50~199.9°C	± 0.2% of rdg + 1 digits	± 0.3% of rdg + 1 digits
	-50~1000°C	± 0.3% of rdg + 1 digits	
	1000~1300°C	± 0.5% of rdg + 1 digits	± 0.5% of rdg + 1 digits
	-58~391°F	± 0.3% of rdg + 2 digits	± 0.5% of rdg + 1 digits
	-58~2372°F	± 0.5% of rdg + 2 digits	± 0.3% of rdg + 2 digits
	T1-T2	-	± 0.3% (T1-T2) of rdg + 2 digits

POWER

9V (6F22) X 1

Standard Accessories : Manual, TP01 Temperature Probe
Dimension : 130(H) x 95(W) x 28(D)mm