

CC-09



Features:

- 5½ Digit LED
- Calibration of AC Volt, Amp Frequency Meters
- Calibration of DC Volt, Amp Meters
- Calibration of Resistance Meters, Clamp & Multi Meters

Technical Data:

Output	Range	Accuracy	Turns Ratio	100 / 1	100 / 1
Voltage	250mV, 1V, 2.5V, 5V, 10V, 25V, 50V, 100V, 250V, 500V, 1000V	DCV: $\pm(0.02\%$ of reading + 0.01% FS) ACV: $\pm(0.05\%$ of reading + 0.02% FS)	Input Max.	5A	10A
			Current	500A	1000A
Current	100μA, 500μA, 2.5mA, 10mA, 25mA, 100mA, 250mA, 1A, 2.5A, 10A, 50A	DCI: $\pm(0.03\%$ of reading + 0.02% FS) ACI: $\pm(0.05\%$ of reading + 0.03% FS)	Clamp Jaw	> 20mm	> 28mm
			DC Impedance	0.7Ω	0.9Ω
Frequency	50Hz, 60Hz, 400Hz, 1kHz	<0.1%	DC Burden	5A / 3.5V	10A / 2.5 V
			AC Burden	5A / 6V	10A / 5V
Resistance	10, 24, 50, 100, 240, 500(Ω) 1, 2, 4, 5, 10, 25 (kΩ) 10x1k, 24x1k, 50x1k 100x1k, 240x1k, 500x1k, 1kx1k, 2.4kx1k, 5kx1k, 10kx1k, 24kx1k	$\pm(0.2\%$ of reading + 20mΩ)	Frequencies	DC to 60Hz	DC to 60Hz
			Accuracy	$\pm 0.3\%$ rdg	$\pm 0.3\%$ rdg

Special Function :

Stability	DC : <0.01%FS / 3 min. AC : <0.02%FS / 3 min.
Ripple	<0.2%
Power Supply	230V AC, 50 (60) Hz
Distortion	<0.5%

- Standard Accessories : Key Adjuster, Power Cord, Pair of Output Leads 50A, Briefcase, Optional Accessories Standard Current Coil
- Dimension : 190(L) x 480(W) x 545(H)mm

FG - 5Kg/FG - 20Kg/FG - 100Kg



Features:

- Dual Display

MODEL	FG - 5Kg	FG - 20Kg	FG - 100Kg
Force Range	$\pm 5\text{kgf}$	$\pm 20\text{kgf}$	$\pm 100\text{kgf}$
	$\pm 5000\text{gf}$		
Resolution	$\pm 49\text{N}$	$\pm 196\text{N}$	$\pm 980\text{N}$
	$\pm 11\text{Lbf}$	$\pm 44\text{Lbf}$	$\pm 220\text{Lbf}$
Accuracy	0.001kgf	0.01kgf	0.01kgf
	1gf		
Measurement State	0.01N	0.1N	0.1N
Display	0.01Lbf	0.01Lbf	0.1Lbf
Power Off	$\pm 0.1\%$ FS ± 1 Digit		
Backlight	Peak Value Measurement, Real Time Measurement		
Safe Load	2 Reversed 4 Digit Led		
Data Output	10 Minutes Auto Power off, Manual Power Off		
Power	Blue Backlight		
Surrounding	150% FS(Buzzer arm Over 110%FS)		
Dimension	USB, Bluetooth (99 Groups)		
	AA 1.5V X 2 (UM-3) or 6V DC		
	No Vibration Source of Corrosive Medium Around		
	211(H)x80(W)x36(D)mm		