0 611 911 1F0 – GBH 180-LI

Material number	0 611 911 1F0
EAN	4059952518657
2 x battery GBA 18V 4.0Ah 1 600 Z00 163	\checkmark
Auxiliary handle 1 602 025 08X	\checkmark
Carrying case	\checkmark
Depth stop 1 613 001 003	\checkmark
Machine cloth spare part number: 1 619 200 413	\checkmark
Quick charger GAL 18V-40 Professional 1 600 A01 9RJ	\checkmark



Technical data

Technical data

Drilling range

concrete

Noise level

Hammer drilling diameter range in concrete Recommended drilling diameter range in

Max. drilling diameter in metal

Max. drilling diameter in wood

Noise/vibration information

Impact energy (according to EPTA 05/2016)	2 J
Impact rate at rated speed	0 – 5,100 bpm
Rated speed	0 – 1,800 rpm
Weight excl. battery	2.3 kg
Tool holder	SDS plus
Tool dimensions (width)	101 mm
Tool dimensions (length)	325 mm
Tool dimensions (height)	220 mm
Battery capacity	4,0 Ah
Battery voltage	18.0 V
Weight incl. battery	2,9 kg
Charge current	4,0 A
Product category subdivision	Cordless Rotary Hammer with SDS plus

4 – 20 mm

6 – 10 mm

The A-rated noise level of the

13 mm 30 mm

SDS LI-ION plus (STEM COOL PACK CHISEL AMP Share LED LIGHT 00000 00000 00000 00000 00000 2 VARIABLE ATION CONTR SOFT GRIP SDS plus BRUSHLESS MOTOR VARIO-LOCK



BOSCH

power tool is typically as follows: Sound pressure level 90 dB(A); Sound power level 101 dB(A). Uncertainty K= 3 dB.

Sales information

Positioning

Powerful cordless rotary hammer within reach – brushless motor for a lasting performance

User benefit

- Powerful impact system with 2.0 J, 3 mode hammer for versatile usage
- Reduced maintenance due to brushless motor and increased runtime per battery charge
- No sparks and less heat generation during use thanks to brushless motor

