

Material number	0 601 072 VK0
EAN	4059952524603
2 x 1.5 V LR6 battery (AA)	✓
Manufacturer's certificate	✓



Technical data

Technical data

Laser diode	515 nm, < 1 mW
Measuring range, up to	50,00 m
Measurement range	0.05 – 50.00 m
Laser class	2
Measurement accuracy, typical	± 1.5 mm* (*plus use-dependent deviation)
Measurement range of incline measurement	0 – 360° (4 x 90°)
Measuring accuracy (typical)	± 0.2°* (*plus use-dependent deviation)
Measurement time, typical	< 0.5 s
Measurement time, max.	4 s
Power supply	2 x 1.5 V LR6 (AA)
Automatic deactivation	5 min
Weight, approx.	0.2 kg
Units of measurement	m/cm, ft/inch
Memory capacity (values)	30
Dust and splash protection	IP 65
Tripod thread	1/4"
Laser colour	Green



Sales information

Positioning

- Outstandingly robust: 2-in-1 laser measure with green laser for rough jobsites

User benefit

- Integrated 360° tilt sensor for easy angle / inclination measurement, an added versatility to the laser measure
- Intuitive user interface with additional supportive features (favourite button, colour display, help function) makes handling convenient
- Ideal for demanding jobsites thanks to IP 65 protection, and shock-absorbing rubber casing