## Product data sheet





Point Laser

### GPL 3 G



The robust and compact 3-point laser with highly visible green laser points

The most important data

Working range	up to 30 m
Accuracy	± 0.35 mm/m* (except bottom laser point); ± 0,7 mm/m* (bottom laser point) (*plus use-dependent deviation)
Self-levelling range	± 4°

**Part Number** 0 601 066 N00

#### > More product information

# Technical data

#### Technical data

Laser diode	< 1 mW, 500 – 540 nm
Operating temperature	-10 - 45°C
Storage temperature	-20 - 70°C
Laser class	2
Working range	up to 30 m
Accuracy	± 0.35 mm/m* (except bottom laser point); ± 0,7 mm/ m* (bottom laser point) (*plus use- dependent deviation)
Self-levelling range	± 4°
Levelling time	4 s
Dust and splash protection	IP 65
Power supply	2 x 1.5 V LR6 (AA)
Operating time (max.)	8 h
Tripod thread	1/4"
Weight, approx.	0.35 kg
Projection	3 points

# Invented for life

## Product data sheet

#### Power tools for trade & industry

# Advantages:

- Green laser points provide up to four times better visibility than red points
- Durable design for tough conditions: rubberised housing with recessed glasses, IP65 dust and water jets protection
- Integrated rotation mount with strong magnets for fast and secure mounting



























