

0 601 9J5 1L0 – GSB 18V-150 C

Material number	0 601 9J5 1L0
EAN	4059952574493
L-BOXX 136 1 600 A01 2G0	✓
L-BOXX inlay for tool	✓



Technical data

Technical data

Torque (soft/hard/max.)	84/100/150 Nm
No-load speed (1st gear / 2nd gear)	0 – 550 / 0 – 2,200 rpm
Battery type	Lithium-Ion
Max. impact rate	30.000 bpm
Chuck capacity, min./max.	1.5 / 13 mm
Weight excl. battery	2.2 kg
Torque settings	25+2
Tool dimensions (width)	73 mm
Tool dimensions (length)	210 mm
Tool dimensions (height)	220 mm
Battery voltage	18.0 V
Torque (max)	150 Nm
Product category subdivision	Cordless Combi
BITURBO	Yes

Drilling diameter

Max. drilling diameter in wood	150 mm
--------------------------------	--------

Screw diameter

Max. screw diameter	13 mm
---------------------	-------

Noise/vibration information

Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level 94 dB(A); Sound power level 105 dB(A). Uncertainty K= 5 dB.
-------------	---



Sales information

Positioning

- When strength counts – the clever impact drill driver for unrivalled power and control

User benefit

- Extremely fast work progress through a powerful brushless motor with a maximum torque of 150 Nm and ProCORE18V batteries
- Precise Leveling Function and switchable KickBack Control enable unrivalled control at each work stage
- Reliable and robust thanks to metal drill chuck and metal gearbox