0 601 9H5 0F0 - GSR 18V-50

Material number	0 601 9H5 0F0
EAN	4059952576220
2 x battery GBA 18V 2.0Ah 1 600 A00 1CG	1
L-CASE	\checkmark
Quick charger GAL 18V-40 Professional 1 600 A01 9RM	\checkmark



Technical data

Technical data

Torque (soft/hard/max.)	28/50/50 Nm
No-load speed (1st gear / 2nd gear)	0 – 460 / 0 – 1,800 rpm
Battery type	Lithium-Ion
Chuck capacity, min./max.	1.5 / 13 mm
Weight excl. battery	1 kg
Torque settings	20+1
Tool dimensions (width)	63 mm
Tool dimensions (length)	181 mm
Tool dimensions (height)	229 mm
Battery voltage	18.0 V
Torque (max)	50 Nm
Product category subdivision	Cordless Drill/Driver













AMP Share

Drilling diameter

Max. drilling diameter in wood	35 mm
Consultant of an	
Screw diameter	
Max. screw diameter	10 mm
Noise/vibration information	
Noise level	The A-rated noise level of the power tool is typically as follows: Sound pressure level 88 dB(A); Sound power level 99 dB(A). Uncertainty K= 5 dB.



Sales information

Positioning

Robust brushless motor for durability

User benefit

- Intelligent brushless motor for efficiency, endurance, and compactness
- Robust metal chuck and compact ergonomic design ideal for heavy-duty jobs
- Professional 18V System works with Bosch batteries and chargers of the same voltage

