

PM-6102/PM-6105/PM-6115/PM-6130/PM-6175

Features:

- Psi / in H₂O / Mbar
- 11 Pressure Ranges
- Auto Pressure Off (APO)
- Backlight LCD

Unit	PM-6102		PM-6105		PM-6115		PM-6130		PM-6175	
	Range	Res.	Range	Res.	Range	Res.	Range	Res.	Range	Res.
inH2O	±55.40	0.01	±138	1	±415.2	0.1	±830	1	±2078	1
Psi	±2.000	0.001	±5.000	0.001	±15.00	0.01	±30.00	0.01	±75.00	0.1
mbar	±137.8	0.1	±344.7	0.1	±1034	1	±2608	1	±5168	1
KPa	±13.79	0.01	±34.47	0.01	±103.4	0.1	±206.8	0.1	±517.1	0.1
inHg	±0.407	0.001	±1.018	0.001	±30.54	0.01	±61.08	0.01	±15.00	0.1
mmHg	±103.4	0.1	±258.5	0.1	±775.7	0.1	±1551	1	±3878	1
ozin²	±32.00	0.01	±80	1	±240.0	0.1	±480.0	0.1	±1200	1
ftH2O	±4.612	0.001	±11.53	0.01	±34.60	0.01	±69.2	0.1	±173.0	0.1
cmH2O	±140.6	0.1	±351.5	0.1	±1055	1	±2109	1	±5272	1
kgcm²	±0.140	0.001	±0.351	0.001	±1.055	0.001	±2.109	0.001	±5.250	0.001
bar	±0.137	0.001	±0.344	0.001	±1.034	0.001	±2.068	0.001	±5.138	0.001
Max. Pressure Psi	10 Psi		20 Psi		100 Psi					
Accuracy	±0.3% FS									
Linearity/Hysteresis	±0.1% FS									
Repeatability	±0.25% FS									
Pressure connector	1/8" (3.18mm) quick connector									
Over range indication	ERR1 or ERR2									
Power	9V (6F22) X 1									



- Standard Accessories : Soft Carrying Case, Soft Tube, 2 Pcs, Manual, Soft / Hard Tube 2 Pcs, Metal Gas Mouth 2 Pcs
- Dimension : 140(H) X 20(W) X 50(D)

PM-6202 / PM-6205

Features:

- Large Dual LCD with backlight
- Data hold
- Max./Min. Average value with relative time stamp
- Zero adjust, offset & Different function
- Auto Power off
- Low battery indication
- USB Computer Interface
(Advanced Software program for all windows)
- Power : 9V (6F22) X 1



Unit	PM-6202/6205		Unit	
	Range	Resolution		
inH ₂ O	55.40	0.01	Accuracy	±0.3% FSO (25oC)
Psi	2.000	0.001	Repeatability	±0.2%
mbar	137.8	0.1	Linearity/Hysteresis	±0.29% FSO
KPa	13.79	0.01	Pressure Range	± 2 psi
inHg	4.072	0.001	Maximum Pressure	± 10 psi
mmHg	103.4	0.1	Response Time	0.5 Seconds typical
ozin ²	32.00	0.01	Low battery Indicator	Yes
ftH ₂ O	4.612	0.001	Over range indicator	Err.1
cmH ₂ O	140.6	0.1	Under range indicator	Err.2
kgcm ²	0.140	0.001	Operating Conditions	0 to 50oC
bar	0.137	0.001	Storage Conditions	-10 to 60oC
Display	Dual LCD		Power	9V (6F22) X 1

- Standard Accessories : Hard Carrying Case, Tube, Manual, USB Cable & Software.
- Dimension : 210(H) x 75(W) x 50(D)mm

