



# Data Sheet

## RISH Clamp SOLAR True RMS Digital Clamp Meter



Measure



Control



Record



Analyze

### Application

RISH Clamp SOLAR measures important electrical parameters like AC Current (TRMS), DC Current, AC Voltage (TRMS) and DC Voltage. It also features Capacitance, Ohm & Continuity, Frequency and Duty cycle and temperature measurement.

### Product Features

#### Unique Design

Rish Clamp SOLAR is a highly innovative design for features those increases safety and comfort of user.

- Rotating clamp jaws facilitate the measurement at physically awkward positions, vertical bus bars, conductors placed at positions difficult to access.
- Clamp jaws can be opened or closed with the trigger placed at bottom side away from the jaws. This allows the user to place his/her hand at safer distance from live conductor. This greatly reduces exposure of human beings to electrical shocks
- Location and design of trigger eliminates fatigues caused by single finger operation. It allows spreading the force required to open the jaws over more than one finger to ensure comfortable operation.
- Comfortable operation of push buttons and function selector switch, in adverse field conditions.

#### Large Jaw Opening

For Rish Clamp SOLAR Jaw opening of 51mm for standard wire diameter of 50mm .

#### Narrow Body

Narrow housing for firm grip and easy to carry.

#### High Accuracy for low current measurement

The clamp meter can measure accurately at not only the High currents but also Low current ranges.

#### True Root Mean Square (TRMS) measurement

Clamp meter measures AC signal's root-mean-square value accurately irrespective of the shape of input waveform.

#### Measurement on Variable Frequency Drives

The clamp meter can measure accurately on variable frequency drives (VFD) and UPS.

#### User selectable Backlit : (Optional)

It is possible to conduct measurement using the clamp meter during night time in darkness with the help of Backlit. The back lit can be switched ON or OFF by pressing a single key.

#### Temperature measurement

Temperatures from -200 to 800 °C using Pt 100 and Pt 1000 sensors.

#### AUTO POWER OFF

In order to save the power of the Batteries, the clamp meter will automatically shut OFF if it detects no activity for 10 minutes.

#### Analog Scale

Analog scale that updates at the rate 20 times/sec to observe fluctuations in input.

#### CONTINUOUS ON MODE

In this mode, AUTO POWER OFF is disabled

#### DATA Hold Function

By pressing DATA HOLD button, reading on the display can be latched for Hands free operation.

#### MIN,MAX Function

By pressing MIN/MAX button, the clamp meter will start recording latest Minimum and Maximum readings

#### NULL ZERO Correction for Resistance

For Low ohm measurement, the lead resistance can be compensated by pressing the shift key (Yellow Key)

#### NULL ZERO Correction for Capacitance

Null zero correction for capacitance. For nF range, stray capacitance can be compensated by shift key (Yellow Key)

#### AUTO and MANUAL ranging modes

range with best resolution depending on the applied input. In MANUAL ranging mode range is user selectable using MAN Key

#### Diode Measurement

For testing diode and transistors, diode measurement function is available.

#### Protection from dust and water

IP20 for terminals as per IEC60529

#### Applicable International Safety standards

600 V CAT IV/1000V CAT III as per International Safety standard IEC 61010-1-2010

#### Double molded Cover for soft touch and firm grip of the Instrument



Measure



Control



Record



Analyze

### Technical Specifications

Measuring function	Measuring range	Resolution	Input impedance	Intrinsic error of digital display ± (...% of rdg + ...digit) at reference condition	Over load capacity <sup>1)</sup>	
					Over load value	Overload duration
V DC	30.00 mV	10 μV	>10 GΩ // <40pF	0.5 + 3 <sup>2)</sup>	1500 V DC 1000 V AC eff / rms Sine wave	Continuously
	300.0 mV	100 μV	>10 GΩ // <40pF	0.5 + 3		
	3.000 V	1 mV	11 MΩ // <40pF	0.25 + 3		
	30.00 V	10 mV	10 GΩ // <40pF	0.25 + 3		
	300.0 V	100 mV	10 GΩ // <40pF	0.25 + 3		
	1500 V	1 V	10 GΩ // <40pF	0.35 + 3 (upto 1000 V) 0.5 + 3 (1000 V to 1500 V)		
V ~	3.000 V	1 mV	10 GΩ // <40pF	0.75 + 2 (10....300 Digit) 0.75 + 1 (> 300 Digit)		
	30.00 V	10 mV	10 GΩ // <40pF			
	300.0 V	100 mV	10 GΩ // <40pF			
	1000 V	1V	10 GΩ // <40pF			
Ω			No load voltage			
	30.00 Ω	10 mΩ	Max. 3.2 V	0.5 + 3 <sup>2)</sup>	1500 V DC1000 V ACeff / rms Sine wave	10 Sec
	300.0 Ω	100 mΩ	Max. 3.2 V	0.5 + 3		
	3.000 KΩ	1Ω	Max. 1.25 V	0.4 + 1		
	30.00 KΩ	10 Ω	Max. 1.25 V	0.4 + 1		
	300.0 KΩ	100 Ω	Max. 1.25 V	0.4 + 1		
	3.000 MΩ	1 KΩ	Max. 1.25 V	0.6 + 1		
30.00 MΩ	10 KΩ	Max. 1.25 V	2.0 + 1			
Diode →	2.000 V	1 mV	Max. 3.2 V	0.2 + 3		
A AC/DC	300.0 A	0.1 A	-	2 % + 0.5 A	1600 A	Continuously
	1500 A	1 A	-	2 % + 5 A (upto 1200A)		
				2.2 % + 5 A (1200A to 1500A)		



Measure



Control



Record



Analyze

Measuring Function	Measuring range		Resolution	Discharge resistance	U <sub>o</sub> max.	Intrinsic error of digital display ± (...% of rdg + ...digit) at reference condition	Over load capacity <sup>1)</sup>	
							Over load value	Overload duration
F	30.00 nF		10 pF	250 KΩ	2.5 V	1.0 + 3 <sup>2)</sup>	1500 V DC1000 V ACeff / rms Sine wave	10 Sec
	300.0 nF		100 pF	250 KΩ	2.5 V	1.0 + 3		
	3.000 μF		1nF	25 KΩ	2.5 V	1.0 + 3		
	300.0 μF		10 nF	15 KΩ	2.5 V	3.0 + 3 (upto 30 uF) 5.0 + 6 (30 uF to 300 uF)		
Hz				f min V DC	f min V ~		3 kHz 1000 V30 kHz;300 V100 kHz30 V	Continuously
	300.0 Hz		0.1 Hz	1 Hz	45 Hz	0.5 + 3 <sup>3)</sup>		
	3.000 KHz		1 Hz	1 Hz	45 Hz	0.5 + 1 <sup>3)</sup>		
	30.00 KHz		10 Hz	10 Hz	45 Hz			
100.0 KHz		100 Hz	100 Hz	100 Hz				
%	2.0....98.0%		0.1%	2 Hz	-	2 Hz... 1kHz ± 5 Digit <sup>4)</sup> 1 kHz ... 10 kHz; ± 5 Digit / kHz <sup>4)</sup>		
°C	Pt 100	200.0... +200.0 °C	0.1 °C	-	-	2 Kelvin + 5 Digit <sup>5)</sup>	1500 V DC1000 V AC eff / rms Sine wave	10 Sec
		200.0... +850.0 °C	0.1 °C			1.0 + 5 <sup>5)</sup>		
	Pt 1000	100.0... +200.0 °C	0.1 °C	-	-	2 Kelvin + 2 Digit <sup>5)</sup>		
		200.0... +850.0 °C	0.1 °C			1.0 + 2 <sup>5)</sup>		

- At 0° .... + 40 °C
- With zero adjustment, without zero adjustment + 35 digits
- Range :  
3 V ac/dc : U<sub>e</sub> = 1.5 V eff/rms ... 100 V eff/rms  
30 V ac/dc : U<sub>e</sub> = 15 V eff/rms ... 300 V eff/rms  
300 V ac/dc : U<sub>e</sub> = 150 V eff/rms ... 1000 V eff/rms
- On the range 3 V dc, square – wave signal positive on one side  
5 ... 15 V, f = const., not 163.84 Hz or integral multiple.
- Without sensor

#### Reference conditions for Accuracy

Reference temperature	23°C ± 2K
Relative Humidity	45%...55% RH
Waveform of measured quantity	Sinusoidal
Input frequency	50 or 60 Hz ±2%
Battery Voltage	8 V ± 0.1 V

#### Environmental

- Operating temperature -10 to +55°C
- Storage temperature -20 to +70°C
- Relative humidity 0... 90% non condensing
- Terminal Protection IP50 for Housing and IP20 for terminals

#### Battery

- Battery Voltage 9 V DC
- Battery type Manganese Dioxide Cell as per IEC6F22 , alkaline manganese cell as per IEC 6LR 61
- Battery Life Minimum 220 hours on Vdc, Adc, 80 hours on Vac, Aac.

#### Display

- Number of digits 3 ¾ digits.
- Maximum count 3100 counts.
- Over range indication "OL" is displayed.
- Polarity indication "—" sign is displayed for DC functions, if positive pole is at "┴".



Measure



Control




Record



Analyze

### Influence Quantities and Variations

Influence Quantity	Range of Influence	Measured Quantity/ Measuring Range	Variation <sup>1)</sup> ± (...% of rdg. + ...digits)
Temperature	0 °C +21 °C and +25 °C...+40°C	30/300 mV DC	1.0 + 3
		3...300 V DC	0.15 + 1
		1500 V DC	0.4 + 1
		V ~	0.4 + 2
		30 Ω <sup>2)</sup>	0.15 + 2
		300 Ω	0.25 + 2
		3 KΩ – 3 MΩ	0.15 + 1
		30 MΩ	1.0 + 1
		30 nF <sup>2)</sup> – 3 μF	0.5 + 2
		300 μF	4.0 + 2
		Hz	0.5 + 1
		%	± 5 digits
		-200...+200 °C	0.5 K + 2
		+200...+850°C	0.5 + 2
		1500 A ~/ A	0.3 X Specified accuracy + 10
Frequency of the measured quantity	> 65 Hz...400 Hz	3...300 V ~	2.0 + 3
	>400 Hz...1 KHz		
	>65 Hz ...1 KHz	1000 V ~	3.0 + 3
	15Hz ...<45 Hz	A ~	1.0 % of range + 1
	>66 Hz...400 Hz		
Wave form of the measured quantity <sup>3)</sup>	Crest factor CF	1...3	± 1 % of rdg
		1...5	± 3 % of rdg
Battery Voltage	 <sup>5)</sup> ... < 7.9 V > 8.1 V ... 10.0 V	V DC	2 Digit
		V~	4 Digit
		AAC/ADC	8 Digit
		30Ω / 300 Ω/°C	4 Digit
		3 kΩ – 30MΩ	3 Digit
		nF, μF	10 Digit
		Hz	10 Digit
		%	10 Digit
Relative Humidity	75%	V~, VDC A~, ADC Ω F Hz % C	1 x intrinsic error
	3 Days Meter off		
HOLD	-	-	± 1 digits
MIN/MAX	-	V AC/DC , A ~ , ADC	± 2 digits
EMC	-	-	6 % of range



Measure




Control



Record



Analyze

- 1 With temperature: Error data apply per 10 K change in temperature.  
For Aac/Adc error data apply per K change in temperature.  
With frequency: Error data apply to a display from 300 digits onwards.
- 2 With zero adjustment.
- 3 With unknown waveform (crest factor CF > 2), measure with manual range selection
- 4 With the exception of sinusoidal waveform.
- 5 After the “” symbol is displayed.

### Applicable Standards

EMC	IEC/EN 61326-1: 2020 Class B
Immunity	IEC/EN 61326-1: 2020 IEC 61000-4-2 8 KV atmosphere discharge, 4 KV contact discharge. IEC 61000-4-3 : 3 V/m IEC 61000-4-8 : 3 A/m

### Safety

	IEC 61010-1-2010
IP for water & dust	IEC60529
Pollution degree	2
Installation category	III 1000V, IV 600V
High Voltage Test	6.7 kV AC, 50Hz for 1 minute between housing and input. 3.7 kV AC, 50Hz for 1 minute between housing with jaws and input

**Weight** 0.6 Kg

### Standard Scope of supply

- 1 Cable Set
- 1 Battery Set
- 1 Operating Instructions Manual
- 1 Leather carrying case

### Ordering code

- **CL40-1NZ0000000000** - Rish clamp solar 1500V AC/DC, 1500AAC/DC with normal tips probe
- **CL40-1FZ0000000000** - Rish clamp solar 1500V AC/DC, 1500AAC/DC with fine tips probe



Measure



Control



Record



Analyze



RISHABH

All specifications are subject to change without notice



Measure



Control



Record



Analyze

## RISHABH INSTRUMENTS LIMITED

Domestic (India): +91 253 2202028/99 | [marketing@rishabh.co.in](mailto:marketing@rishabh.co.in)

International: +91 253 2202004/06/08/99 | [global@rishabh.co.in](mailto:global@rishabh.co.in)

[www.rishabh.co.in](http://www.rishabh.co.in)