


2 608 657 409 – Reciprocating saw blade S 1225 VF

Material number 2 608 657 409

EAN 3165140451963



Technical data



Description

Specification	Heavy for Metal
Product text, Accessories grey	S 1225 VF BIM, vario-pitched teeth Medium-thick to thick sheet metals (2.5-10 mm), thin-walled and thick-walled pipes and profiles (<250 mm). Ideal for demolition work in metal. Effortless, fine cut.
Packaging type	Paper / Cardboard / Corrugated board - Packaging, pocket, with Euro hole
Pack quantity	5 Pcs
Minimum order quantity	1 Pcs

Areas of application

Sheet metals, thick [mm]	2-10
Pipes/profiles, thin-walled: open+closed [mm]	<250
Pipes/profiles, thick-walled: open+closed [mm]	<250
Profiles, pipes: closed [mm]	<250
Profiles, pipes: open [mm]	<250

Details

Tooth design	Vario toothing
Tooth spacing [mm]	1.8-2.6
Tooth pitch [TPI]	10-14
Total length [mm]	300
Total length [Inch]	12
Width [mm]	19
Thickness [mm]	1.25
Blade material	BI-METAL
Blade material abbreviation	BIM
Body material	HCS
Recommended min. material thickness [mm]	2.5
Recommended max. material thickness [mm]	10
Max. cut capacity [mm]	250
Areas of application	Medium-thick to thick sheet metals (2-10 mm), thin-walled and thick-walled pipes and profiles (<250 mm). Ideal for demolition work in metal. Effortless, fine cut.
Type	S 1225 VF

Appropriate for

Materials that can be processed (Detail)	Metal sheet Steel/ferrous metal Epoxy Glass-fibre reinforced plastic (GRP)
--	---