



Contact Rotation / Linear
Speed Measurement



Wide Measurement Range
Non Contact 10-99999 RPM
Contact 1.0-19999 RPM



MAX / MIN / AVG Function



USB Interface



5 digit, Large Screen LCD



High / Low Threshold Alarm



Low Battery Indication



Auto Power Off

FEATURES :

- ☒ WIDE MEASUREMENT RANGE AND HIGH RESOLUTION
- ☒ ACCURATE SPEED MEASUREMENT
- ☒ LARGE SCREEN LCD DISPLAY
- ☒ AUTOMATICALLY RECORDS THE MAXIMUM, MINIMUM, AVERAGE AND LAST MEASURED VALUES
- ☒ LOW BATTERY INDICATOR
- ☒ HIGH AND LOW THRESHOLD ALARMS
- ☒ EASY AND COMFORTABLE TO USE
- ☒ PHOTOELECTRIC SPEED MEASUREMENT
- ☒ CONTACT ROTATION SPEED MEASUREMENT
- ☒ CONTACT LINEAR SPEED MEASUREMENT
- ☒ USB INTERFACE

• **Auto Power Off** : After 15 Mints.

• **Power Consumption** : Less than 80mA

MEASURING RANGES		RESOLUTION	ACCURACY
NON-CONTACT	10-99999 rpm	0.1rpm(10-9999.9 rpm) 1 rpm (above 10000 rpm)	± (0.05% +1)
CONTACT	1.0-19999 rpm	0.1rpm(1-9999.9 rpm) 1 rpm (above 10000 rpm)	
DISPLAY		5 DIGIT 40 MM LCD	
EFFECTIVE DISTANCE		50MM -500MM	
RANGE SELECTION		AUTOMATIC	

POWER : 700 mAH LITHIUM BATTERY

Dimension	: H184 x W60 x D33 mm
Weight	: Approx. 140 Gms.
Accessories	: Reflective Tape 600mm Long, Contact Linear Speed Accessories 1 Pc, Contact Speed Accessories 3 PCs,