

UNI-T.

UT673A/UT675A BATTERY TESTER



12V/24V

UT673A

UT673A/UT675A battery testers can be used to analyze the battery health of automobile batteries, suitable for battery capacities from 3 to 250Ah. These CE certified testers can rapidly and accurately detect common faults caused by battery. UT675A also includes USB communication and built-in printer for report generation.




12V cranking lead acid battery test



12/24V charging or cranking system test



Display battery capacity, voltage, resistance and life



Four-terminal Kelvin test



10 types of battery standards



Language option (Chinese/English)



Test without battery disassembly



LED color indication for test result (UT673A)



Print on-line and real-time test reports (UT675A)



USB data transfer (UT675A)



Petrol car



Diesel car



Motorcycle



Electrical motorbike

	Range	UT673A	UT675A
Certificates	CE, FCC, RoHS		
12V battery test	7~16V DC	√	√
12V/24V cranking system test	7~30V DC	√	√
12V/24V charging system test	7~30V DC	√	√
Battery type	Ordinary lead acid battery, AGM flat plate battery, AGM spiral battery, GEL battery, EFB battery		
Battery capacity	3~250Ah	√	√
Battery standard and range	CCA: 40~2000; BCI: 40~2000; CA: 40~2000; MCA: 40~2000; JIS: 26A17~24SH52; DIN: 40~1400; IEC: 40~1400; EN: 40~2000; SAE: 40~2000; AH: 3~250AH		
Over voltage protection		√	√
Reverse connection protection		√	√
A prompt of poor contact		√	√
Battery status display		√	√
Battery life display		√	√
Battery capacity display		√	√
Battery internal resistance display		√	√
USB communication			√
Printing function			√
Power	None, powered by external source		
Display	128*64 black and white lattice		
Product net weight	UT673A: 264g; UT675A: 413g		
Product size	UT673A: 76mm x 22mm x 142mm; UT675A: 95mm x 47mm x 183mm		