

The UT714 is powerful temperature calibrator that sources and measures thermocouples, RTDs, voltage, and resistance. It can be used to test and calibrate different types of temperature instruments. This device is suitable for testing input/output temperature terminals such as sensors and transmitters.



UT714

Type	Range	Accuracy
Certificates	CE, UKCA	
Measurement		
DC voltage (V)	50mV/500mV/30V	±(0.02%+2)
Resistance (Ω)	500Ω/5000Ω	±(0.05%+10)
Thermocouples	R,S,K,E,J,T,N,B,L,U	
RTDs	Pt100/Pt200/Pt500/Pt1000/Cu10/Cu50/Cu100/Pt100-392/Pt100-JIS/Ni120	
Continuity test	✓	
Source		
DC voltage (V)	100mV/1000mV/10V	±(0.02%+10)
Resistance (Ω)	400Ω/4000Ω	±(0.05%+10)
Thermocouples	R,S,K,E,J,T,N,B,L,U	
RTDs	Pt100-385/Pt100-392/Pt100-JIS/Pt200-385/P500-385/Pt1000-385/Cu10/Cu50/Cu100/Ni120	
Display count	20000	
Operating temperature	-10°C~55°C	

Features	
Step/ramp functions	Source and measure accuracy up to 0.02%
Rechargeable battery	Contrast adjustment
Auto power off (Time adjustable)	Stores and recalls setups
USB communication	

Characteristics	
Standard accessories	Test leads, USB cable, power adapter, temperature probe, English manual
Power	1.2V x 6 AA rechargeable battery
Product size	195 x 95 x 58mm
Product net weight	650g
Standard individual packing	Gift box, carrying bag
Standard quantity per carton	1pc
Standard carton measurement	305 x 85 x 260mm
Standard carton gross weight	1.5kg