

CM-2090

Features:

- 3000 A • 5,999 Count
- SMART AC Digital Flexible Clamp.
- Ø 75mm.
- Clamp Torch with Blacklight.

DC VOLTAGE

Range	Resolution	Accuracy
6V	0.001V	±0.8% of rdg + 3 digits
60V	0.01V	
600V	0.1V	

AC VOLTAGE

Range	Resolution	Accuracy	
		45~65Hz	40~2000Hz
6V	0.001V	± 1.2% of rdg + 3 digits	± 2.0% of rdg + 5 digits
60V	0.01V		
600V	0.1V		

FREQUENCY

Range	Resolution	Accuracy
40 - 1000Hz	0.1Hz	±0.5% of rdg + 2 digits
1kHz - 10KHz	1Hz	

AC CURRENT

Range	Resolution	Accuracy		
		40~65Hz	65~400Hz	400~1000Hz
60A	0.01A	± 3.0% of rdg + 5 digits	± 3.0% of rdg + 5 digits	-
600A	0.1A		± 3.0% of rdg + 5 digits	
3000A	1A		<1000A ± 3.0% of rdg + 5 digits	

- Standard Accessories : Soft Carrying Case, Test Lead, Manual
- Dimension : 324(H) x 178(W) x 30(D)mm



RESISTANCE

Range	Resolution	Accuracy
6kΩ	0.001kΩ	±1.0% of rdg + 3 digits
60kΩ	0.01kΩ	
600kΩ	0.1kΩ	
6MΩ	0.001MΩ	

POWER AAA 1.5V X 3