

**FEATURES :**

- ☒ 3½ DIGIT
- ☒ 1,999 COUNT
- ☒ JAW OPEN : 52 MM
- ☒ AUTO POWER OFF (APO)
- ☒ TRUE RMS
- ☒ MAX / MIN / RELATIVE
- ☒ DATA HOLD
- ☒ AUTO / MANUAL RANGE

DC VOLTAGE

RANGE	RESOLUTION	ACCURACY
200mV	0.1mV	±1.0% of rdg ±5 digits
2V	1mV	±0.5% of rdg ±5 digits
20V	10mV	
200V	100mV	
1000V	1V	±1.0% of rdg ±5 digits

DC CURRENT

RANGE	RESOLUTION	ACCURACY
200V	100mA	±2.0% of rdg ±5 digits
1000V	1A	

CAPACITANCE

RANGE	RESOLUTION	ACCURACY
400μF	100mF	±5.0% of rdg ±10 digits
4mF	1μF	
40mF	10μF	

AC VOLTAGE

RANGE	RESOLUTION	ACCURACY
200mV	0.1mV	±1.5% of rdg ±5 digits
2V	1mV	±1.0% of rdg ±5 digits
20V	10mV	
200V	100mV	
750V	1V	±1.5% of rdg ±5 digits

AC CURRENT

RANGE	RESOLUTION	ACCURACY
200V	100mA	±2.0% of rdg ±5 digits
1000V	1A	

RESISTANCE

RANGE	RESOLUTION	ACCURACY
200Ω	0.1Ω	±0.8% of rdg ±5 digits
2kΩ	1Ω	±0.8% of rdg ±3 digits
20kΩ	10Ω	
200kΩ	100Ω	
2MΩ	1kΩ	
20MΩ	10kΩ	±1.2% of rdg ±5 digits

POWER : 1.5V AAA x 2

Dimension	: H185 x W65 x D32 mm
Weight	: Approx. 200 g.
Accessories	: Test leads, Manual, TP04 Thermocouple, Carrying Bag & Battery.
Qty	: 30 Pcs. in a Box.