

Product Specifications

EN

Model		NF-8508	
Cable type		CAT5/CAT6	
Voltage protection		60V	
Battery		Type C charge	
Transmitter	CONT	Wiremap Port	RJ45
		MAX range	300m
		STP/NTP	√
		Digital mode and Analog mode	√
	Scan	Frequency	455KHz
	Port Flash	Full duplex / Half duplex	Automatic Identification
		Auto-Nego / Non-Auto- Nego	
		10m/100m/1000m	
	Length	≤20M+/-1.6M, 20M~100M+/-2.4M, ≥100M+/-3.2M	
	PoE	Standard/Non standard	Automatic Identification
		End connection /Middle jumper / Powered by 8 cores	
		PoE Power supply	Voltage detection
	VFL	10mW	
	Power meter	850/1300/1310/1490/1550/1625 (Wavelength)	
	Crimping	RJ45-8 Cores,Min length is ≥10cm	
	Lower voltage warning	< 3.5V ± 0.1V	
Power supply	3.7V 1500mAh Polymer lithium battery		
Transmitter size	148 X 70 X32 mm		
Recevier	Sensitivity adjustable	√	
	MAX range	300m	
	Digital mode and Analog mode	√	
	MAX working current	≤300mA	
	NCV	√	
	Lamp	√	
	Lower voltage warning	√	
	Power supply	3.7V 1500mAh Polymer lithium battery	
	Receiver size	198 x 50 x 28 mm	