

SOLDRON[®] PLUG VARIABLE WATTAGE SOLDERING IRON



Thank you for purchasing the SOLDRON[®] Plug Variable Wattage Soldering Iron. Please read this manual before use, and keep it after reading it for future reference. This state of art soldering iron has all the features and specifications to match and beat larger and more space-consuming soldering units. Save space and solder more precisely with our latest innovations.

SI15-30A

WARNINGS:

- Always use it in a safe and stable environment, while wearing appropriate safety gear.
- The iron gets very hot. Direct contact with any surface of skin should be avoided.
- Always switch off the unit when not in use.
- Always keep away from children.
- This product is only intended for use with electronic and electrical purposes, by professional and trained personnel

MAIN FEATURES:

- 1. Fitted with a premium-grade, long-life ceramic-coated bit (X10 the life of a standard nickel-plated bit.)
- 2. Reduced length of iron for precision work.
- 3. Best-quality (FR-grade and burn-resistant) 3-core copper wire
- 4. Ergonomically shaped, tri-grip handle with ridges for comfortable, slip-free use
- 5. Solid-state printed ceramic heater; semi-thermostatic Extremely long life and rapid heating

SET UP AND OPERATION:

- 1. Plug in and set the knob provided on the plug to the desired temperature.
- 2. Tin the tip with solder wire prior to the first use.
- 3. Use only a wet sponge to clean the bit.
- 4. Please do not tap or knock the iron to remove excess solder as this can damage the ceramic element.
- 5. Two separate models are available with either a point or a spade as indicated on the box.

STORAGE:

- 1. Please make sure the unit is cooled and switched off before storing.
- 2. Store in a cool, dry place to avoid oxidation and extend the life of the product.
- 3. Always tin the tip of soldering irons prior to first use. Visit the SOLDRON.com FAQ section for more information.

NOTE: Soldron Soldering Irons work best with Soldron spares and accessories.

SPECIFICATIONS:

Model No:	Soldron [®] SI15-30A
Input Voltage	220V AC
Output Temperature	250°C - 480°C
Output Power	15-30 W
Wire Length	3 core mains cord 1.2mtrs
Bit Supplied	CB15-30S3 / CB15-30N3

WARRANTY:

SOLDRON[®] provides a Limited manufacturer warranty for 6 months from the date of purchase. Please see SOLDRON.COM warranty for more information.

Vimla Engineering

A2/157,Shah & Nahar Industrial Estate, S. J. Marg, Lower Parel (W), Mumbai - 400 013. Tel No. : 022-48973383